

Double-sided Tape

KA-5951



General Technical Information

Description& Application

KA-5951 is double coated tape with specially designed high tack adhesive which could provide relatively high initial adhesion, good push strength and good shear holding power to a variety of surfaces, at the same time it has good vibrating resistance ability.

Construction& Properties:

Release Film 25um
Acrylic adhesive
Clear PET Film
Acrylic adhesive
Release Film 75um

		Test Method
Total Thickness	50±5µm	
Appearance	Clear	
Adhesive Type	Acrylic	
Strength of Adhesion to Steel	≥1200g/25mm	ASTM D3330
Test methods& results: Detailed of these methods are available on request. The above figures are averages values, and not recommend to be used for specification purpose.		

Dimensions Availability:

Customer may specify variations, slitting size as well.

Application Features:

Before application the surfaces must be free from oil, fat, dust and solvent liquid.

Storage and Shelf Life:

Store in the original packing at about 25°C and 65% relative humidity, Keep in dark place.

Kingdom recommends use this product within 6 months from date of manufacture, also the product adhesion performance shelf life after processing must be confirmed.

Recommendation: Conditions designed to avoid contamination and scratches on plastic films.

For more information about Kingdom product, please contact at:
+86-755-89959584; or E-mail: menglu@kingdom-film.com