

# Mono-layer Adhesive Tape

## KD1019W



### *General Technical Information*

#### **Description& Application**

KD1019W is Mono-layer coated pressure sensitive adhesive tape. Tape carrier has good insulating properties, Good adhesive performance, long-time adhesion .

#### **Structure**

Silicone Coating
PET Film
Acrylic adhesive

#### **Product Data**

		Test Method
Tape Thickness	50 ± 5um	
Appearance	White	
Adhesive type	Acrylic	
Adhesion	> 1000 gf/25mm	ASTM D3330
PET Release Force	< 8 gf/in	FINAT FTM 3

#### **Dimensions Availability:**

Customer may specify variations, slitting size as well.

#### **Application Features:**

Before application the surfaces must be free from oil, fat, dust and solvent liquid.

#### **Storage and Shelf Life:**

Store in the original packing at about 25 °C and 65% relative humidity, Keep in dark place.

Kingdom recommends use this product within 12 months from date of manufacture, also the product adhesion performance shelf life after processing must be confirmed.

**Recommendation:** Conditions designed to avoid contamination and scratches on plastic films.

For more information about Kingdom product, please contact at:  
+86-755-89959584; or E-mail: [menglu@kingdom-film.com](mailto:menglu@kingdom-film.com)